

Product Information and Data Sheet

Hi-Tech Hydrotel AW SERIES

Anti Wear High Performance Hydraulic Oil

Hitech Hydrotel AW Series hydraulic oils are formulated from base products with high viscosity index and contains suitable additive package. They are designed for systems where mild anti wear protection is needed.

Application

Hitech Hydrotel AW Series hydraulic oil will be used as fluid media for hydraulic systems and hydraulic pumps in stationary as well as mobile Machines under moderate operating conditions. It can also be used for circulation, splash, bath and ring oiling systems of both plain and anti-friction bearings, gears of industrial machinery, chain drives and crankcase lubrication.

Features

Excellent Hydraulic Efficiency

Potentially reduced energy consumption or increased system responsiveness

Good compatibility with elastomers and seals

Long seal life and reduced maintenance

Ultra Keep Clean Performance

Reduced system deposits leading to reduced machine maintenance and increased component life

Anti-wear properties

Helps reduce wear and protects pumps and components for extended equipment life

Excellent Hydraulic Efficiency

Sustained component protection over a wide temperature

Excellent Air Separation Characteristics

Helps prevent aeration and cavitation damage in low residence time systems

Oxidation and Thermal Stability

Extends fluid life even under harsh operating conditions

Multi metal compatibility

Helps ensure excellent performance and protection with a wide variety of component metallurgy

Physical Properties

Hi-Tech Hydrotel AW	32	46	68	100	150	220	320
Viscosity, cSt @ 40 °C	32	46	68	100	150	200	320
Viscosity Index, Min.	95	96	98	98	98	98	98
Flash Point, COC°C Min	191	194	211	211	231	231	252
Pour Point, °C Max	-3	-3	0	0	0	0	0
Rust Test (D-665)	Pass						

Manufactured & Marketed By



Plot#25-A, Raipur Sahakari Industrial Area, Raipur Bhagwanpur, Roorkee, Uttarakhand.

Plot#F-167, RIICO Industrial Area, 3rd Phase, Balotra

Corporate Office

Mandeep Tower, Residency Road, Opp. Sankalp Restaurant, Jodhpur, Rajasthan

Quality at Better Price



FOR INDUSTRIAL USE ONLY KEEP AWAY FROM SUNLIGHT

These oil qualifies Vickers V-104C vane pump test and meet IS:10522-1983 (Reaffirmed 2004) and IPSS 1-09-002

specifications.

Not recommended for lubrication of turbines and machines having white metal, silver or silver coated parts.

